

IN THE CLAIMS:

- 1. (currently amended) A thermoplastic resin composition, comprising:
 - (a) 50 to 95 pbw of a thermoplastic resin component comprising an aromatic polycarbonate resin a thermoplastic resin;
 - (b) 0 to 15 pbw of an organophosphorus flame retardant compound; and
 - (cb) 0.10 to 20 pbw of a flame-retarding amount of a polyimide compound, each based on 100 pbw of the thermoplastic resin component, organophosphorus compound, and polyimide compound.
- (currently amended) The composition of claim 1 comprising 1 to 15 pbw of the
 organophosphorus flame retardant compound-wherein the thermoplastic resin comprises
 a polyearbonate.
- 3. (currently amended) The composition of claim 2 wherein the thermoplastic resin component further comprises a vinyl aromatic graft copolymer.
- 4. (currently amended) The composition of claim [[1]]2 wherein the composition additionally comprises a organophosphorus flame retardant compound having has the formula:

$$R_{6}-(O) = P - O + X - O - P - (O)_{d} - P - R_{9}$$

$$(O) \qquad (O) \qquad (O)$$

wherein R_6 , R_7 , R_8 and R_9 are each independently aryl, halo aryl or (C_1-C_6) alkyl substituted aryle, X is arylene, halo arylene or (C_1-C_6) alkyl substituted arylene, a, b, c and d are each independently 0 or 1, and n is an integer from 0 to 5, more preferably from 1 to 5.

5. (canceled)

- 6. (currently amended) The composition of claim [[5]]4 wherein the thermoplastic resin composition further comprises a vinyl aromatic graft copolymer.
- 7. (currently amended) The composition of claim 6.1 wherein the polyimide is a polyetherimide and has the formula:structural units of the formula:

wherein the divalent T moiety bridges the 3,3', 3,4', 4,3', or 4,4' positions of the aryl rings of the respective aryl imide moieties; T is -O- or a group of the formula -O-Z-O-; Z is a divalent radical selected from the group consisting of formulae:

wherein X is a member selected from the group consisting of divalent radicals of the formulae;

USPTO CENT. FAX.

wherein y is an integer from 1 to about 5, and q is 0 or 1; R¹⁰ is a divalent organic radical selected from the group consisting of:

VPC


- (a) aromatic hydrocarbon radicals having from 6 to about 20 carbon atoms and halogenated derivatives thereof,
- (b) alkylene radicals having from 2 to about 20 carbon atoms,
- cycloalkylene radicals having from 3 to about 20 carbon atoms, and (c) divalent radicals of the general formula:

where Q is a member selected from the group consisting of formulae:

$$-c_{\gamma}H_{2\gamma}-$$
, $-c_{\gamma}H_{2\gamma}-$, $-c_{$

where y' is an integer from about 1 to about 5.

- 8. (original) The composition of claim 7 wherein the polycarbonate is a polycarbonate comprising bisphenol-A.
- 9. The composition of claim 8 wherein T is derived from bisphenol-A. (original)
- The composition of claim 9 wherein R¹⁰ is (original) 10.



- 11. (new) A thermoplastic resin composition, comprising:
 - (a) 50 to 95 pbw of a thermoplastic resin component comprising an aromatic polycarbonate resin and a vinyl aromatic graft copolymer;
 - 1 to 15 pbw of an organophosphorus flame retardant compound; and **(b)**
 - 0.10 to 20 pbw of a flame-retarding amount of a polyimide compound, each based on 100 pbw of the thermoplastic resin component, organophosphorus compound, and polyimide compound.
- (new) The composition of claim 11 wherein the thermoplastic resin component 12. comprises, based on 100 pbw of the resin component, 30 to 95 pbw of the polycarbonate, 1 to 70 pbw of the vinyl aromatic graft copolymer, and optionally an additional thermoplastic resin.
- (new) The composition of claim 11 wherein the organophosphorus flame retardant 13. compound has the formula:

wherein R6, R7, R8 and R9 are each independently aryl, halo aryl or (C1-C6)alkyl substituted aryl, X is arylene, halo arylene or (C1-C6) alkyl substituted arylene, a, b, c and d are each independently 0 or 1, and n is an integer from 0 to 5, more preferably from 1 to 5.

(new) The composition of claim 11 wherein the vinyl aromatic graft copolymer is an 14. ABS copolymer.

15. (new) The composition of claim 11 wherein the polyimide is a polyetherimide and has structural units of the formula:

wherein the divalent T moiety bridges the 3,3', 3,4', 4,3', or 4,4' positions of the aryl rings of the respective aryl imide moieties; T is -O- or a group of the formula -O-Z-O-; Z is a divalent radical selected from the group consisting of formulae:

wherein X is a member selected from the group consisting of divalent radicals of the formulae:

wherein y is an integer from 1 to about 5, and q is 0 or 1; R¹⁰ is a divalent organic radical selected from the group consisting of:



- (a) aromatic hydrocarbon radicals having from 6 to about 20 carbon atoms and halogenated derivatives thereof,
- (b) alkylene radicals having from 2 to about 20 carbon atoms,
- (c) cycloalkylene radicals having from 3 to about 20 carbon atoms, and divalent radicals of the general formula:

where Q is a member selected from the group consisting of formulae:

$$-c_{\gamma}H_{2\gamma}-$$
, $-c-$, $-s-$ and $-s-$

where y' is an integer from about 1 to about 5.

- 16. (new) The composition of claim 15 wherein the polycarbonate is a polycarbonate comprising bisphenol-A.
- 17. (new) The composition of claim 16 wherein T is derived from bisphenol-A.
- 18. (new) A method for the manufacture a flame retardant thermoplastic resin composition, comprising combining
 - (a) 50 to 95 pbw of a thermoplastic resin component comprising an aromatic polycarbonate resin and a vinyl aromatic graft copolymer;
 - (b) 1 to 15 pbw of an organophosphorus flame retardant compound; and
- (c) 0.10 to 20 pbw of a flame-retarding amount of a polyimide compound, each based on 100 pbw of the thermoplastic resin component, organophosphorus compound, and polyimide compound.